






Battery System Designed For PV Household Application

Battery Series SMILE5-BAT



✓ Key Features

-  **Modular**
-  **Plug & play**
-  **Safe**
-  **Long lifespan**



CHEMISTRY

AlphaESS only goes with LFP for safest operation and longest cycle-life

Whilst Alpha's batteries are slightly larger per physical capacity versus other types of Li-Ion used in electronics and EVs, they are easily banked in parallel close together because they don't suffer heat issues and thermal runaway. We have chosen LiFePO4 for their superior life, safety and environmental performance.

About AlphaESS


As one of the earliest pioneers in energy storage market with lithium iron technology, AlphaESS has a vision to pave the path for everyone in the world to enjoy clean energy one day.

AlphaESS is a multinational company that currently has more than 10'000 residential and commercial systems running in 30 countries globally and its products are accredited by IEC, TÜV, CEC and many other international standards.

All AlphaESS energy systems are integrated with smart energy management solutions. AlphaESS is committed to revolutionize the future energy network through our patented German technologies.



immersa
www.immersa.co.uk

Physical	
Model	SMILE5-BAT
Battery Type	LFP (LiFePO4)
Battery Manufacturer	 EVE ENERGY VERY ENDURE
System Weight	65 kg
Dimension (W x D x H)	600 x 250 x 600 mm
IP Protection	IP21 (Indoor) / IP65 (Outdoor)
Warranty	10 Year Battery Warranty
Electrical	
Energy Capacity	5.7 kWh
Usable Capacity	5.5 kWh
Depth of Discharge (DoD)	96%
Nominal Voltage	51.2 V
Operating Voltage Range	48 ~ 57.6 V
Internal Resistance	≤ 30 mΩ
Cycle Life	10 000*
Operation	
Max. Charging Current	56 A (0.5C)
Max. Discharging Current	56 A (0.5C)
Max. Short-circuit Current	200 A
Operating Temperature Range	-10 °C ~ 50 °C**
Humidity	15% ~ 85%
BMS	
Modules Connection	1 ~ 6 in parallel
Capacity Range	5.7 / 11.5 / 17.2 / ... / 34.4 kWh
Usable Capacity Range	5.4 / 10.9 / 16.3 / / 32.7 kWh
Monitoring Parameters	System voltage, current, cell voltage, cell temperature, PCBA temperature
Communication	CAN and RS-485 compatible
Certification	
Transportation	UN38.3
Safety	IEC 62619 (Cell), IEC 62619 (Pack)

*Under specific test conditions

**When the temperature is below 0 °C or above 40 °C, the performance will be limited.



For further information and order enquiries contact us below

Immersa
Suite 4F, Drake House,
Long Street, Dursley
GL11 4HH

T 44 (0)1453 545222
E info@immersa.co.uk

